



Mobilize Your Enterprise®



Mobility Sales/Technical Center

17681 Mitchell N
Irvine, CA 92614
O 949.222.0300
T 877.278.7860
F 949.222.0375

Headquarters/Main Warehouse

2312 Touhy Avenue
Elk Grove Village, IL 60007
O 847.818.1260
T 877.278.7860
F 847.818.1287

Infinite Peripherals Canada

677 MacDonald Avenue, Unit #210
Sault Ste Marie, ON
P6B 1J4 Canada
O 705.943.1808
E canada [at] ipcprint.com

ipcmobile.com

Specifications subject to change without notice. Infinite Peripherals, Mobilize Your Enterprise, Linea Pro, Infinea, Infinea Tab and Infinea Omni are trademarks of Infinite Peripherals, Inc. All other trademarks are the property of their respective owners.

© 2018 Infinite Peripherals, Inc.

Linea Pro 7

GENERAL SPECIFICATIONS

► FEATURES

STANDARD FEATURES	Li-ion Battery, Lightning Connector, Bi-directional MSR
OPTIONAL FEATURES	1D Barcode Laser, 2D Barcode Imager, SRED Capable MSR, RFID, Bluetooth (SPP/iAP)

► MECHANICAL

COMPATIBILITY	iPhone 6, iPhone 6s, iPhone 7
DIMENSIONS (LxWxH)	1D and 2D Scanner (LxWxH): 157 mm x 77 mm x 26 mm (6.2 in x 3 in x 1 in)
WEIGHT	148 grams (5.2 oz.) without iOS Device
PORT	Charge and Sync via USB connection

► ELECTRICAL

BARCODE SCANNER	1D Laser or 2D High Speed Imager (supports all major 1D or 2D barcodes)
BATTERY CAPACITY	2100mAh battery
BATTERY LIFE	Up to 16,850 scans in a period approximately 26 hours on a full charge (depending on use)
CARD READER	3-track bidirectional Magnetic Stripe Reader (MSR) / Type: ISO 7810, 7811, 7813
CONTACTLESS: RFID (OPTIONAL)	MIFARE and ISO compatible (see User Manual for details).
ENCRYPTION & KEY MANAGEMENT (OPTIONAL)	AES 128/256, 3DES DUKPT
BLUETOOTH	Bluetooth 2.0 compatible - Class 2 (option) - Serial Port Profile (SPP)
INDICATOR	Visual: 4 LEDs for battery status Audio: Electromagnetic Buzzer

► CERTIFICATIONS

CERTIFICATIONS	Apple MFi / FCC, PCI PTS 3.x SRED (optional)
-----------------------	--

► ENVIRONMENTAL

OPERATING ENVIRONMENT	Temperature: -10°C to +40°C (14°F to +104°F) Humidity: 5% to 90% RH
STORAGE ENVIRONMENT	Temperature: -20°C to +50°C (-4°F to +122°F) Humidity: 5% to 90% RH