

MP22



Connected via NFC & Bluetooth

Mobilize Your Enterprise®



Pay. Process. Print.
All from the palm of your hand.

Introducing the MP22 Mobile Printer. This 2-inch device fits in the palm of your hand and is fully equipped to handle rapid, mobile printing transactions. With a sleek, compact design, long lasting battery, and flexible communication features, the MP22 mobilizes your business to process receipts anywhere, anytime.

High-Speed Processing:

100 mm per second printing speed makes the MP22 one of the fastest mobile printers. With such rapid processing power, you can print and process receipts quickly and efficiently.

Durable, Light, Compact:

This device fits in the palm of your hands and is even smaller than most cell phones! Sleek and durable, the MP22 is structurally designed for hand-held, mobile use.

Connect and Communicate:

With flexible communication features, you can easily pair your MP22 printer to other mobile devices. Each device comes with a standard USB interface. Additional, Near Field Communication (NFC) functions enable WiFi and latest Bluetooth compatibility.

Long Lasting Battery:

55-hour battery life allows you to take your transactions on the go without the constant need to charge! Device also features a 2-hour rapid recharge.

Built-in Sensor:

With a built-in smart sensor, your MP22 will alert you to paper end, lid open, and low battery. This printer will stay alert while you continue growing your business.

Suitable for Many Industries:

This compact printer is perfect for printing receipts and barcodes across all industries including food delivery, hospitality, transportation, and delivery. Simple and durable, the MP22 is fully equipped to mobilize your enterprise.

ACCESSORIES (Coming Soon)



MP22

Connected via NFC & Bluetooth

FEATURES

MODEL	MP22
INTERFACE	Standard USB
	Option Bluetooth Smart Ready Ver 4.2 or Wi-Fi (802.11 a/b/g/n)
COMPATIBILITY	Window Printer Driver(10, 2012, 8.0/8.1, 7, 2008, Vista, 2003, XP, 32 & 64bit), Windows (CE 4.2 & 5.0 & 6.0 & 7.0 / Mobile 5.0 & 6.0)

PRINTING SPECIFICATIONS

PRINTING	Method	Direct Thermal
	Speed	100mm / sec
DOT DENSITY		203 DPI
DOT PITCH		8dots /mm, 0.125 pitch
EFFECTIVE PRINTING WIDTH		48mm, 384dots/line
CHARACTER PER LINE	Font A(12 x 24) 32 columns Font B(9 x 17) 42 columns	
PAPER	Type	Thermal Paper
	Width	Max, 58mm
	Thickness	0.06mm
	Roll Diameter	Max, \varnothing 40mm
	Roll Core Inner	12.5 \pm 0.5mm
CHARACTER SET	Alpha Numeric Character	95
	Extended Graphic	128 x 18page (1 space page)
	International Character	14
FONTS		FontA(12x24), FontB(9x17), Asian Font(KOR,JPN, CHN_GB2312,CHN_BIG5), Font0/1/2/4/5/6/7, Resident TTF, Downloadable TTF, FontA-H, FontGS, Resident TTF(Font0), Font1 - 8

MECHANICAL

DIMENSION		80mm x 119.4mm x 44mm (W x D x H)
WEIGHT		242.5g (with battery)
RELIABILITY	TPH Life	50km
	Pulse Activation	50,000,000 pulse or more (12.5% Print Ratio)

MECHANICAL continued

BARCODE	1D	EAN-8,EAN8(+2+5), EAN-13, EAN13(+2+5), Codabar, Code11, Code39, Code93, Code128, ITF, LUPC-A(+2+5), UPC-E,UPC-E(+2+5), Planet, UPC-A etc.
	2D	QR, PDF417, MicroPDF417, Maxicode, Datamatrix, Aztec, RSS14, TLC39
SENSOR		Paper end, Cover open, Black mark

ELECTRICAL

EMULATION	ESC/POS, CPCL, ZPL
BATTERY	7.4V 1510mAh Li-ion,
BATTERY CHARGER	AC/DC Charger
BATTERY LIFE	55 hrs stand-by
BATTERY CHARGING TIME	2 hrs
MEMORY	Flash 8mb SD RAM 8mb

CERTIFICATIONS

DROP RESISTANCE	1.5m
IP RATING	IP42 certified

ENVIRONMENTAL

OPERATING ENVIRONMENT	Temperature: -10 - 50°C Humidity: 35 - 80%
STORAGE ENVIRONMENT	Temperature: -20 - 60°C Humidity: 10 - 90%

ipcmobile.com



**Headquarters/
Main Warehouse**
2312 Touhy Avenue
Elk Grove Village, IL 60007
O 847.818.1260
T 877.278.7860
F 847.818.1287



**Mobility
Innovation Center**
17681 Mitchell N.
Irvine, CA 92614
O 949.222.0300
T 877.278.7860
F 949.222.0375

Specifications subject to change without notice. Infinite Peripherals, Mobilize Your Enterprise, Linea Pro, Infinea, Infinea Tab and Infinea X are trademarks of Infinite Peripherals, Inc. All other trademarks are the property of their respective owners.